

Technical Data

Dimensions and weights		TSW 4190 S	TSW 5210 S	TSW 5210 W	TSW 6240 S	TSW 6240 W	TSW 7340 S
		Tandem	Tandem	Tandem	Tandem	Tandem	Tridem
Gross vehicle weight	kg	16,000 – 19,000	16,000 – 22,000	16,000 – 22,000	24,000	24,000	34,000
Dead weight	kg	6,320	7,310	8,100	8,940	9,300	11,160
Payload	kg	9,680 – 12,680	8,690 – 14,690	7,900 – 13,900	15,060	14,700	22,840
Bridge dimensions							
Length	mm	5,600	5,900	5,900	6,900	6,900	7,900
Width	mm	2,050	2,050	2,050	2,050	2,050	2,050
Height	mm	1,070	1,320	1,320	1,320	1,320	1,320
Vehicle dimensions							
Length	mm	8,200	8,450	8,450	9,400	9,400	10,400
Width	mm	2,550	2,550	2,550	2,550	2,550	2,550
Height	mm	3,250	3,300	3,440	3,300	3,300	3,300
Transfer height series	mm	2,600*	3,000**	3,060**	3,065**	3,085**	3,065**
Load capacity	m ³	14.00	17.00	17.00	19.70	19.70	23.00
Power requirements	KW	88 – 147	103 – 184	103 – 184	118 – 221	118 – 221	147 – 294
	HP	120 – 200	140 – 250	140 – 250	160 – 300	160 – 300	200 – 400

* with tire 650/50 R 22.5 Nokian

** with tire 710/50 R 26.5 BKT

Optional:

- ALB – automatic load sensitive brake system
- Forced steering (hydraulic or computer controlled)
- Lift axle
- Side wall extensions
- Beater spreader unit with cardan drive
- Spread pattern limiter
- Various lighting possibilities
- BCT20 comfort controls
- ISOBUS comfort controls
- Weighing system
- Central lubrication
- Various tire options, etc.

