

## Technical Data

		GTW 21	GTW 25	Optional:
Chassis		Standard chassis with DLB	Tandem chassis with DLB	
Bin dimensions (length x width)	mm	4,800 × 2,550	4,800 × 2,550	Tires:
<b>Vehicle dimensions:</b>				550/60-22.5 (only GTW 25)
Length*	mm	7,400 – 7,900	7,400 – 7,900	600/55-22.5 (only GTW 25)
Width*	mm	2,990	2,650 – 3,000	700/50-22.5 (only GTW 25)
Loading height*	mm	3,200	3,320 / 3,740**	600/55-26.5 (only GTW 25)
Capacity (DIN)	m <sup>3</sup>	21	21 / 25**	700/50-26.5 (only GTW 25)
<b>Max gross weight:</b>				600/55 R 26.5 Michelin CARGO XBIB (only GTW 25)
Road	kg	12,000	20,000 – 22,000	710/50 R 26.5 Michelin CARGO XBIB (only GTW 25)
Field use	kg	21,000	24,000	30.5/R 32 (v GTW 21)
Transfer conveyor loading height*	mm	4,800	4,920	ALB (only GTW 25)
<b>Conveyor diameter:</b>				low drawbar
Feeder conveyor	mm	350	350	ball coupling
Transfer conveyor	mm	400	400	tarpaulin w/without platform

\* depending on equipment | \*\* when equipped with body extension



Manure Spreaders - Universal Spreaders - Loading and Silage Trailers - Forage Transport Trailers - Grain Transfer Trailers - Vario Systems - Special Vehicles

# BERGMANN

*...the specialists*

Ludwig Bergmann GmbH · Maschinenfabrik

Hauptstraße 64-66 · 49424 Goldenstedt/Germany

PROFIAGRAK DOO  
 PRODAJNO SERVISNI CENTAR  
 SALAŠ br 4, 21214 Sirig, SRBIJA  
 Tel: +381 21 84 99 00 Tel/fax: +381 27 010 31  
 www.profiagrar.com