

Dimensions and weights

		GTW 330	GTW 430
Length *	mm	9,930	11,690
Width *	mm	2,550-3,000	2,550 – 3,000
Height *	mm	3,975	3,975
Capacity	m ³	30	38.5
Optionally with side wall extensions	m ³	33	43
Side loading height	mm	3,600	3,600
Ø Feeder conveyor	mm	500	500
Ø Transfer Conveyor	mm	600	600
Transfer height max.**	mm	3,625-5,800	3,625 – 5,800
max ***	mm	3,150-5,625	3,150 – 5,625
Transfer width max **	mm	725-3,000	725 – 3,000
max ***	mm	1,315-3,325	1,315 – 3,325
Transfer capacity	t/h	1,100	1,100
Dead weight *	kg	9,800	11,600
Gross vehicle weight	kg		
Street	kg	24,000	34,000
Field use	kg	35,000	48,000
Power demand	KW	132-257	162-294
	hp	180-350	220-400

* Depending on equipment ** without unloading tube extension *** with unloading tube extension

Optional:

Tires:

710/50 R 26.5

750/45 R 26.5

800/45 R 26.5

750/60 R 30.5

800/45 R 30.5

Electro-hydraulic forced steering

Lift axle

Side wall extensions

Weighing system

Pilot box

Unloading tube extension – hydraulic swivel mechanism

Hydraulic cover

Camera systems

Various lighting variations



Manure Spreaders – Universal Spreaders – Loading and Silage Trailers – Forage Transport Trailers – Vario Systems – Special Vehicles

BERGMANN

...the specialists

Ludwig Bergmann GmbH · Maschinenfabrik

Hauptstraße 64-66 · 49424 Goldenstedt /Germany

Tel.: +49 (0)44 44-2008-0 · Fax: +49 (0)44 44-20 08 88



PROFIAGRAR DOO

PRODAJNO SERVISNI CENTAR

SALAŠ br 4, 21214 Sirig, SRBIJA

Tel: +381 21 84 99 00 · Telefax: +381 27 010 46

www.profiagrar.com